

CK-A9008

Features



- *Stand-Alone DVR,H.264 Compression
- *High quality video Display : NTSC (720x480), PAL (704x576) real time display
- *Multiple Recording/ Search Categories:Date/Time, Event, Manual, Schedule, alarm, motion detection
- *Real time recording support: 480 Fps for NTSC at CIF image (400 Fps for PAL)
- *16ch Video recording at the same time
- *Pentaplex: Live, Record, Playback, Back-up and Network at the same time
- *Backup: CD-RW (Option: DVD-RW), USB 2.0 and NET backup supported
- *PTZ camera control in local and remote area
- *E-mail notification
- *3G support
- *With multi-languages menu

Specifications

Model	CK-A9008
Compression Standard	H.264 (ASIC)
Resolution	Preview resolution: 704 x 576 (PAL) , 720 x 480 (NTSC) Playback resolution: 4 x CIF Frames: 1F/S ~ 30F/S (Adjustable)
Real time recording support	720x480 30 Fps for NTSC at D1 image (704x576 25 Fps for PAL)
Hard Disk	2 SATA Hard Disk interface(Support Capacity from 40G to 4T in Total)
Video Signal	PAL (625Line, 50f/s) , NTSC (525Line, 60f/s)
Video Input	8 channel, BNC , 1.0V p-p/75Ω
Composite Video Output	1 channel, BNC, 1.0V p-p/75Ω
Monitor Video Output	1 channel, BNC, 1.0V p-p/75Ω
VGA Interface	1 VGA,Resolution:800x600/60HZ,1024x768/60HZ
Audio Input	2 channel, RCA
Audio Output	1 channel, RCA
Alarm Input	2 Channel, Trigger closed without Voltage, Open or Closed
Alarm Output	1 Channel, Trigger closed without Voltage, Open or Closed
Alarm Mode	Sensor Input, Motion Detection, Video Loss, Full Disk Space.
Network	Ethernet (10/100M)、LAN、WAN and ADSL
Control Way	USB2.0 Mouse, Remote Control, Camera, RS485 x 1
Password	Encrypted by 128-bit Numerical Digits with 2-Level Password Protection
Power Supply	DC12V 3.0A
Consumption	10W (Without HDD)
Working Environment	Temperature: +5℃~+50℃; Humid: < 90%
Device Dimension	350 x 272 x 58mm (W*D*H)
Weight	4.5kgs