

H.264 CIF SERIES 16CH DVR



Specification

| | |
|---------------------------|---|
| Model | AP-7116C |
| Operation System | Embedded Linux OS |
| Video Compression | Main profile H.264 |
| Video Input | 16 CH BNC |
| Video Output | 1 CH BNC,1CH Spot,1 CH VGA(1280 * 1024) |
| Audio Input/Output | 2CH RCA/1 CH RCA |
| Display Picture Division | 1/4/9/16 CH |
| Multiplex operation | Live/Network/Playback/Record/Backup |
| Display Resolution | PAL:D1(704 * 576),NTSC:D1(704 * 480) |
| Recording Mode | Manual/Timer/Motion Detection/Remote |
| Total Recording Resource | D1 @ 100fps,HD1 @ 200fps,CIF @ 400fps |
| Recording Quality | Single channel adjustable |
| Recording Resolution | PAL:D1(704 * 576),HD1(704 * 288),CIF(352 * 288) NTSC:D1(704 * 480),HD1(704 * 240),CIF(352 * 240) |
| Recording Playback | 1/4 ch playback simultaneously |
| Recording Backup | USB Flash Disk,Movable Hard Disk,Built-in DVD Writer(optional),Network |
| Alarm input/output | 8CH/1CH |
| Spot Alarm Pop | Support |
| PTZ | Support PTZ preset,Cruise and control PTZ via PC |
| PTZ Protocol | PELCO-D,PELCO-P |
| HDD | 2TB |
| HDD Storage remark | Support |
| Recording File Play | Special Player |
| Network and Protocol | 1 RJ-45 10/100M ,Support TCP/IP,DDNS,DNS,PPPOE,DHCP,UPNP,NTP |
| IE Browser | Support |
| Client Software/CMS | Support(One software for at most 50 DVRs) |
| Multilanguage OSD | Support |
| Mobile Phone Surveillance | Support Android,iphone,Blackberry,Symbian,Windows CE OS |
| Dual-Stream | Support(Main and secondary interchange) |
| SDK Package | Available |
| Mouse Interface | USB 1.1 |
| Backup Interface | USB 2.0 |
| Remote Controller | Support |
| User Authority | Multi-level user authority |
| Input Method | Support |
| Power | DC 12V/5A |
| Working Temperature | 0°C~50°C |
| Working Humidity | 10%~90% |
| Size (mm) | 34(W)×230(D)×45(H) |
| Accessories | Remote controller , Adapter ,Mouse , User manual , CD with software |