

4CH

Model: AP-7704D



Feature:

1. Adopts the standard Main profile H.264 compression technology,D1 and CIF can be adjusted,
 supports 4ch recording, Network transmission, and playback simultaneously
2. Support dual-stream transmission for all channels
3. Support Multiplex operation: live, record, playback, backup, network transmission, mobile phone surveillance
4. Support backup with USB Flash Disk, Movable hard discus writer, Network
5. Support 1channel. Main output, 1channel. VGA output
6. Support video channel hidden and S.E.Q for single channel
7. Support Digital Zoom and PIP preview
8. Support password watermark function to avoid data modification
9. Support Action with Alarm and pre-alarm recording function
10. Support Email alarm
11. Mobile phone surveillance (Win CE/Symbian/iPhone/Blackberry/Android)
12. Support PTZ preset and Cruise Control
13. Support Multi-language OSD
14. Central management software and Networked system management
15. Support mouse, remote controller, panel operating

Specifications:

Model	AP-7704D
Operating system	Embedded Linux OS
Video Compression Format	Main Profile H.264
Video Input	4 Channels BNC
Video Output	2 Channel BNC, 1 Channel VGA(1280*1024)

Audio Input/Output	4 Channel RCA/1 Channel RCA
Intercom	1 Channel RCA Input, 1 Channel RCA Output
Display Picture	1/4
Digital Zoom、 PIP	Supports
Multiplex Operation	Live/ display/ Playback/ Recording/ Backup/
	Mobile phone Surveillance/ Network simultaneously
Display Resolution	PAL:D1(704*576),NTSC:D1 (704*480)
Recording Mode	Manual/ Timer/ Motion Detection/ Alarm
Recording Frame Rate	D1@100fps,HD1@100fps,CIF@100fps adjustable
Recording Resolution	PAL:D1(704*576),HD1(704*288), CIF(352*288),
	NTSC:D1(704*480),HD1(704*240),CIF(352*240)
Recording Playback	1/4 channel playback simultaneously (Optional playback channel)
Recording Backup	USB、 Moved Hard Disk、 USB Writer、 Network
Network transmission	4Channels real-time Network transmission with CIF resolution
Recording Play	Special player, Support AVI file format conversion
JPEG capture function	Support,3M Pixels@10fps
Alarm input/output	4 channels input, 1 channel output
Action with Alarm	Support
Email Alarm	Send pictures to the designated email
SPOT Alarm pop-up	Support
Video Mask Alarm	Support
PTZ	Supports PTZ preset ,Cruise Control and PC client port setup
PTZ protocol	PELCO-D,PELCO-P
HDD	Support 1 SATA HDD, capacity to 2T
HDD Remain Time Hint	Support
Network and Protocol	1 RJ-45 10/100M via Ethernet, Support TCP/IP、 PPPOE、 DHCP、
	DNS、 DDNS、 SNTP、 NTP、 UPNP
IE Browser	Support
Client Software	Support
CMS	Support(One software for at most 50 DVR), Free supply to use
Dual Stream	Support (Main and secondary interchange)
Group play	At least Support five users online access
Privacy Mask	Support
S.E.Q	Support single channel and grouping S.E.Q
Watermark	Support
Multi-language	Support
Mobile Phone Surveillance	Support Windows/ Symbian/ iPhone/ Blackberry/Android Operation System
SDK Package	Available
Mouse Interface	USB2.0
Backup interface	USB2.0
Remote Controller	Support (Supports controller ID matching)

User Authority	Support Multi-level user authority distribution
Date and time Format	adjustable
DST	Support
Power	DC12V/3A
Working Temperature	0°C-50°C
Working Humidity	10% – 90%
Size(mm)	285mm(W)×220mm(D)×46mm(H)