

Apexis Mini IP Camera APM-J012-WS



Specification:		Model: APM-J012-WS
Image Sensor	Image Sensor	1/4" Color CMOS Sensor
	Display Resolution	640 x 480 Pixels(300k Pixels)
	Lens	f: 6 mm, F:2.0 (IR Lens) (3.6mm lens optional)
	Mini. Illumination	0.5Lux
Lens	Lens Type	Glass Lens
	Viewing Angle	60 Degree (3.6mm lens is 90Degree)
Audio	Input	Built-in Microphone
	Output	1 channel audio output
	Audio Compression	ADPCM
Video	Image Compression	MJPEG
	Image Frame Rate	15fps(VGA),30fps(QVGA)
	Resolution	640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Vertical / Horizontal
	Light Frequency	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
Communication	Ethernet Interface	Build in 10/100Mbps,Auto MDI/MDIX , RJ-45
	Supported Protocol	HTTP,FTP,TCP/IP, UDP, SMTP, DHCP, PPPoE, DDNS, UPnP, GPRS
	Wireless Standard	IEEE 802.11b/g
	Data Rate	802.11b: 11Mbps (Max.), 802.11g: 54Mbps (Max.)
	Wireless Security	WEP & WPA WPA2 Encryption

Physical	Infrared Light	10 IR LEDs, Night visibility up to 10 meters
	Alarm Input	1 Channel on/of, f Input
	Alarm Output	1 Channel relay Output
	Dimension	80(L) x44(W) x80mm(H)
	Gross Weight	App. 600g
	Color Box	180 x 120 x 160 mm
	Net Weight	App. 400g (accessories included)
Power	Power Supply	DC 5V/2.0A (EU,US,AU adapter or other types optional)
	Power Consumption	5 Watts (Max.)
Environment	Operate Temper.	0° ~ 55°C (14°F ~ 131°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temper.	-10°C ~ 60° (14°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing
PC System Requirements	CPU	2.0GHZ or above (suggested 3.0GHz)
	Memory Size	256MB or above (suggested 1.0GHz)
	Display Card	64M or above
	Supported OS	Microsoft Windows 2000/XP/Vista/7
	Browser	IE6.0/7.0/8.0/Firefox/Safari/Google chrome or other standard browsers
Certification	CE, FCC, RoHS	