

KDP-H633SH20

Plastic IR Dome camera

IR LED: ϕ 5X24PCS IR LED working distance: 20M

Lens: Board Lens 3.6mm/F2.0

Dimension: ϕ 94 x 69(H) mm Weight:300g



Model	KDP-H633SH20	KDP-633SH20	KDP-1030SH20
Image Sensor	1/3"SONY	1/3"SONY	1/4"CMOS
TV System	PAL/NTSC		
Horizontal Resolution	480TV Lines Low Illumination 420TV Lines Low Illumination	420TV Lines Low Illumination	480 TV Line
Pixels	PAL:752(H)x582(V) NTSC:768(H)x494(V) PAL:500(H)x582(V) NTSC:510(H)x492(V)		
IR LED	ϕ 5X24PCS		
IR Series Distance	20M		
Lens	Board Lens 3.6mm/F2.0		
Sync System	Internal		
IR Status	Under 10 Lux By CDS		
IR Power On	CDS Auto Control		
Usable Illumination	0.001 Lux/F2.0	0.0005 Lux/F2.0	0.01 Lux/F2.0
S/N Ratio	\geq 48dB (AGC OFF)		
Gamma Correction	0.45		

Video Out	Composite Signal (1.0Vp-p, 75Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
White Balance	Auto
Power Source	DC12V 350mA
Dimension	Φ 94 x 69(H) mm
Weight	300g