# **MDR757**

## 8CH H.264 DVR

**USB Mouse Control with GUI Display** 



### **FEATURES**

#### **USB Mouse Control with GUI OSD**

❖ The GUI OSD interface is provided and used with your USB mouse.

#### **Intelligent Motion Recording**

- Only the channel with an event will be recorded to effectively save a significant amount of hard disk space and have the maximized recording time.
- Supports pre-alarm recording.

#### **Remote Surveillance**

- Mobile surveillance via many popular mobile platforms, such as iPhone, BlackBerry, WinCE, J2ME & Android are supported to fulfill various user demands.
- Network surveillance via the licensed software "Video Viewer", Internet Explorer, Mozilla Firefox or Google Chrome web browser, and QuickTime player is supported with up to 5 users' login simultaneously.

#### **Remote Independent Operation**

Channel switching & video playback are fully independent from the local site, allowing users to have private image monitoring remotely.

#### **H.264 Video Compression Technology**

- Highly improves video quality for live, recording, and network.
- \* Recording file size is minimized for longest recording time.
- Lower bit rate required for fastest network transfer.

#### **Multiplex**

Allows live display, record, playback, backup and network operation at the same time.


#### **Backup Function**

Supports USB flash drive and network backup.

#### **Audio / Video Support**

- ❖ 4 audio-in, 1 audio-out to record sounds.
- ❖ VGA interface built-in.

### **REAR PANEL**



# **SPECIFICATIONS**

Video System		NTSC / PAL (auto detection)
Video Compression Format		H.264
Video Input		8 channels (Composite video signal 1 Vp-p 75 Ω BNC)
Video Output (BNC)		Main Monitor: For stable display
Video Output (VGA)		Built-in VGA interface for LCD monitor
Audio Input / Output		4 audio inputs, 1 audio output (Mono)
Maximum Recording Rate	Frame	704×480 pixels with 60 IPS <ntsc> / 704×576 pixels with 50 IPS <pal></pal></ntsc>
	CIF	352×240 pixels with 240 IPS <ntsc> / 352×288 pixels with 200 IPS <pal></pal></ntsc>
Image Quality Setting		SUPER BEST / BEST / HIGH / NORMAL
Hard Disk Storage		Accommodates 2 SATA HDDs (1 HDD capacity up to 2TB)
Quick Search		Time / Motion / Alarm search mode
SATA Interface		Built-in
Recording Mode		Manual / Timer / Motion / Alarm / Remote
Multiplex Operation		Live display / record / playback / backup / network operations
USB Mouse Control		YES
Motion Detection Area		16 × 12 grids per channel
Motion Detection Sensitivity		3 adjustable parameters for accurate detection
Pre-alarm Recording		YES
Backup Device		USB 2.0 flash drive / Network
Web Transmitting Compression Format		H.264
Ethernet		10/100 Base-T. Supports remote control and live view via Ethernet
Web Interface		Licensed software "Video Viewer" / Internet Explorer, Mozilla Firefox
		or Google Chrome web browser / QuickTime player
		(5 users access simultaneously)
		*Operating System: Windows 7 / Vista / XP / 2000
Network Protocol		TCP/IP, PPPOE, DHCP and DDNS
Basic Remote Independent Operation		YES
Event Notification		By FTP & E-Mail
R.E.T.R. (Remote Event Trigger Recording)		YES
IR Remote Control		YES (IR receiver built-in)
Mobile Surveillance		YES (Including iPhone, BlackBerry, WinCE, J2ME & Android)
Picture Zoom		2X digital zoom
PTZ Control		YES
Alarm I/O		8 inputs, 1 output
Key Lock (Password Protection)		YES
User Level		Administrator & Operator
Video Loss Detection		YES
Camera Title		Supports up to 6 letters
Video Adjustable		Hue / Saturation / Contrast / Brightness
Date Display Format		YY/MM/DD, DD/MM/YY & MM/DD/YY
Daylight Saving		YES
Power Consumption (±10%)		DC 19V
Power Consumption (±10%)		< 64 W
Operating Temperature		10°C ~ 40°C (50°F ~104°F)
Dimensions (mm)**		432(W) × 90(H) × 326(D)
System Recovery		System auto recovery after power failure
Optional Peripherals		Keyboard Controller

<sup>\*</sup>The specifications are subject to change without notice.
\*\* Dimensional tolerance: ±5mm