

IR Waterproof Camera: SA-1512



* Image Sensor	1/3" SONY SUPER HAD CCD
* Resolution	420TVL~600TVL(Optional)
* Lens	3.6mm Board Lens, 2.8mm/6mm Lens (Optional)
* LED	∅ 5mm×23PCS
* IR Distance	20m
* Waterproof	IP66
* Bracket	3 Axis Bracket

Model	SA-1512		
Image Sensor	1/3" Sony SUPER HAD CCD		
TV System	PAL/NTSC		
Effective Pixel	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:752(H)×582(V) NTSC:768(H)×494(V)	PAL:795(H)×596(V) NTSC:811(H)×508(V)
Horizontal Resolution	420TVL	540TVL	600TVL
Minimal Illumination	0.1Lux/F1.2 0Lux(IR On)		0.001Lux/F1.2 0Lux(IR on)
Synchronous System	Internal Synchronization		
S/N Ratio	>48dB	>54dB	
Electronic Shutter	1/50-1/60,000s(PAL) 1/60-1/60,000s(NTSC)		
White Balance	ATW		
BLC	On		
AGC	Auto		
Gamma Adjusting	0.45		
Video Output	1.0Vp-p at 75Ω		
Lens	3.6mm Board Lens, 2.8mm/6mm Lens (Optional)		
LED	∅ 5mm×23PCS		
IR Distance	20m		
Power Supply	DC 12V/ 300mA		
Working Temperature	-10°C~+50°C RH90% MAX		
Dimension(mm)	50mm×85mm×60mm		
Weight(g)	220g		