

6610P

Main Features

- 1 / 4" SONY SUPER HAD CCD, 480TVL
- 128 presets points / 6 tours
- 360°Auto Tracking Function
- 10X optical zoom, 3.78~37.8mm
- OSD Menu
- Remote upgrade the software through RS 485



6610P-A
Wall-mounted



6610P-B
Hoisting



6610P-C
Ceiling-mounted



6610P-D
Embedded

TECHINICAL SPECIFICATIONS

| Model | Intermediate Speed | High-Speed |
|------------------------------|---|---------------------|
| Power Supply | 12V±10% | |
| Operation Temperature | -20°C ~ +60°C | |
| Humidity | ≤95% no dew | |
| Power Consumption | 20W | |
| Communication Mode | RS485 | |
| Baud Rate | 2400/4800/9600/19200 bps | |
| Horizontal Rotate Speed | 5°~100° (1~64shift) | 5°~180° (1~64shift) |
| Horizontal Rotate Range | 360° rotation | |
| Pitching Range | 90° | |
| Auto Flip Function | Auto Flip 180°when Vertical 90° | |
| Auto Control Focus Speed | Auto adjustment according to focus change | |
| Two Spots Scanning | At random | |
| Two Spots Scan Speed | 1~8 optional | |
| Two Spots Scan Dwelling Time | 1~60sec.optional | |

| | |
|-------------------------------------|------------------|
| Preset Position Number | 128 |
| Speed to Patrol Point | 1~8 optional |
| Every Preset Position Dwelling Time | 1~60sec.optional |
| Scouting Group | 6 |
| Scouting Spots in every Group | 16 |

KB-001

Main Features

- Set the address range of the dome camera and the decoder: 0~255.
- Control all functions of the dome camera, such as: BLC ON/OFF.
- To operate the speed dome camera at different speed.
- To operate PTZ horizontal Scanning automatically in different speed and direction
- Set or call the preset locations and cruise tracks of the dome camera. Altogether 128 preset locations and 6 cruise tracks can be set. Each track involves 16 preset locations and the dwelling time and call speed upon each point can be set as well.
- Control the dome camera manually or automatically, and change the internal settings of special camera by opening the camera menu.
- Control the focus, zoom and iris manually.



TECHINICAL SPECIFICATIONS

| | |
|--|---|
| Model | Speed Dome Camera PTZ Controller |
| Communication between Speed Dome Camera and Controller | Port to Multi-port and Half Duplex Function |
| Communication Connector | RS-485/RS-232 output |
| Baud Rate | 2400,4800,9600,and 12000Bps |
| Communication Protocol | PELCO-D/PELCO-P |
| Distance of Communication | 1200M |
| Control of Capacity | Up to 32 Cameras |
| Power Supply | DC12V/1000mA±10% |
| Dimension | 440x190x98 mm |