

**TAYAMA**



## KIR-673CN20

IR LED:  $\phi$  5X24PCS IR LED working

distance: 20M Built-in bracket 3-Axis direction bracket

Water resistance:IP66 Cable built-in bracket

Lens: Board Lens 3.6mm/F2.0

Dimension:175(W) x69(H) x55(D)mm Weight:820g



<b>Model</b>	<b>KIR-673CN20</b>											
IMAGE DEVICE	1/3" SONY Super HAD CCD											
SCANNING SYSTEM	PAL											
NUMBER OF PIXELS	NTSC:811(H)x508(V) PAL:795(H)x596(V)											
SYNC. SYSTEM	INTERNAL											
RESOLUTION	700 TV LINE											
MINIMUM ILLUMINATION	0.001 Lux/ F2.0											
S/N RATIO	MORE THAN 48dB(AGC off)											
SUPPLY VOLTAGE	DC 12V											
GAMMA CORRECTION	0.45											
GAIN CONTROL	AUTO											
EXPOSURE	AUTO ELECTRONIC SHUTTER 1/60(1/50)~1/100000											
OSD SET	<table border="1"> <tr> <td>EXPOSURE</td> <td></td> <td></td> </tr> <tr> <td>BR.LEVEL</td> <td></td> <td></td> </tr> <tr> <td>AGC</td> <td></td> <td></td> </tr> </table>			EXPOSURE			BR.LEVEL			AGC		
EXPOSURE												
BR.LEVEL												
AGC												

			AGC LIMIT		
			BACKLIGHT		
			HLM		
			MIRROR		
			DAY/NIGHT		
			M-DET		
			EXIT		
			Control-by-Wire		

VIDEO OUTPUT 1.0 Vp-p COMPOSITE VIDEO. 75(OHM) LOAD

POWER CONSUMPTION	)	150mA(+/-10%)		
-------------------	---	---------------	--	--

OPERATION TEMP. From -10°C TO 55°C

LENS TYPE	3.6mm
-----------	-------

DIMENSION 38x38mm