



TAYAMA

WI-HT40

Metal Housing Weatherproof IP66

2.8-12mm Manual Zoom Lens (2M pixels)

IR Led & Range: Φ 5X42PCS 40M

Camera: 220(W)x80(H)x80(D)mm

NW: 1100g/pc

Specification

Model	WIS70-HT40	WIH70-HT40	WIS65-HT40	WIH60-HT40	WIS42-HT40
Image Sensor	Color 1/3" SONY	Color 1/3" SHARP	Color 1/3" SONY	Color 1/3" SHARP	Color 1/3" SONY
Horizontal Resolution	700TVL, Low Illumination, DWDR, OSD, DNR, Effio-E	700TVL, Low Illumination, DWDR, OSD, DNR	650TVL, Low Illumination, DWDR, OSD, DNR	600TVL, Low Illumination	420TVL, Low Illumination
Pixels	NTSC:768(H)x494(V), PAL:752(H)x582(V)	NTSC:768(H)x494(V), PAL:752(H)x582(V)	NTSC:768(H)x494(V), PAL:752(H)x582(V)	PAL:752(H)x582(V), NTSC:768(H)x494(V)	PAL:752(H)x582(V), NTSC:768(H)x494(V)
TV System	PAL/NTSC				
IR LED	Φ 5X42PCS				
IR Series Distance	40M				
Lens	2.8-12mm Manual Zoom Lens (2M pixels)				
Sync System	Internal				
Usable Illumination	0.001Lux/F2.0	0.001Lux/F2.0	0.001Lux/F2.0	0.001Lux/F2.0	0.0005Lux/F2.0
S/N Ratio	\geq 115dB (AGC OFF)	\geq 115dB (AGC OFF)	\geq 52dB (AGC OFF)	\geq 52dB (AGC OFF)	\geq 48dB (AGC OFF)
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75 Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec				

Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
White Balance	Auto
Power Source	DC12V 300mA
Dimension	220(W)x80(H)x80(D)mm
Weight	1100g
Package	16pcs/carton 59*35*49mm