



WPD-MB

Outdoor Mini PTZ Speed Dome camera

Weatherproof Outdoor IP66

Pan range: 0°~360° Continue (Not 355°)

Tilt range: 0°~90° Flip / Auto flip 180°

Pan Speed: Max 200°/sec

Preset: 256, 4 pattern scans, 8 cruise line

RS485, Pelco D/P supported

Built-in full-screen OSD

Camera: Ø147.5x167.6mm

NW: 2200g/pcs

Specification

Model	WPD-S70MB	WPD-S65MB	WPD-S48MB
Image Sensor	Color 1/3" SONY	Color 1/3" SONY	Color 1/3" CMOS
Horizontal Resolution	Sony EFFIO-S DSP 700TVL	Sony Effio 650TVL	SONY 480TVL
Pixels	NTSC:976(H)×494(V), PAL:976(H)×582(V)	NTSC:768(H)×494(V), PAL:752(H)×582(V)	PAL:752(H)×582(V), NTSC:768(H)×494(V)
TV System	PAL/NTSC		
Power	DC 12 Volts, 800mA		
White Balance	Auto		
Lens	10X(f=3.8~38mm)		
Usable Illumination	0.001Lux/F2.0	0.001Lux/F2.0	0.0005Lux/F2.0
S/N Ratio	≥115dB (AGC OFF)	≥52dB (AGC OFF)	≥48dB (AGC OFF)
Gamma Correction	0.45		
Video Out	Composite Signal (1.0Vp-p, 75Ω)		
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec		
Electronic Shutter Time	Auto:PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec		
Operation Temperature	-10°C ~ +50°C RH95% Max		
Storage Temperature	-20°C ~ +60°C RH95% Max		